

序号	品名	材质
①	0.5无盖立式胶芯(H4.0)	LCP UL94V-0 本色
②	0.5无盖立式端子(H4.0)	铜合金/表面镀锡
③	0.5无盖立式焊片(H4.0)	铜合金/表面镀锡

技术指标:

- 塑件表面应光洁、无毛边、无明显收缩、缺陷、裂纹等现象.
- 温度范围: $-25^{\circ}\text{C}\sim+85^{\circ}\text{C}$.
- 额定电压: 50V, AC/DC(等效).
- 接触电阻: $\leq 0.03\Omega$.
- 绝缘电阻: $\geq 500\text{M}\Omega$
- 产品料号:

LW0540-***
NO OF CKT (产品PIN数) *
Plating (电镀方式) *
0: 端子全雾锡
1: 端子全金 (G/F OVERALL)
Packing (包装方式)
T: TUBE管装
R: TAPE & REEL卷装

CKT (0.5mm pitch)	BO	W	F
4	5.30	16	7.5
5	5.80		
6	6.30		
7	6.80		
8	7.30		
9	7.80		
10	8.30		
11	8.80		
12	9.30		
13	9.80		
14	10.30	24	11.5
15	10.80		
16	11.30		
17	11.80		
18	12.30		
19	12.80		
20	13.30		
21	13.80		
22	14.30		
23	14.80		
24	15.30		
25	15.80		
26	16.30		

NOTE(注):

- 1.10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE $\pm 0.2\text{mm}$.
(10片孔距累积公差 $\pm 0.2\text{mm}$.)
2. CARRIER CAMBER NOT TO EXCEED 1mm IN 100mm.
(载带拱/弧形MAX: 1/100mm.)
3. ALL DIMENSIONS MEET EIA-481 REQUIREMENTS.
(所有的尺寸要满足协会EIA-481规范.)
4. MATERIAL: CLEAR ANTISTATIC PS, COLD SEALING.
(载带材料: 透明抗静电 PS.)
5. THICKNESS: $0.30\pm 0.05\text{mm}$. (载带厚度: $0.30\pm 0.05\text{mm}$.)
6. PACKING LENGHT PER REEL: 16.32 METERS. (每卷包装长度: 16.32米.)
7. COMPONENT LOAD PER REEL: 2000 PCS. (每卷包装数量: 2000只.)
8. 纸箱装箱以不超过装箱线为准, 空余位置用塑料泡沫及保尼龙填充.
9. 纸箱分小、中、标准型3种规格型号: 装箱为整箱(左下包装量)采用标准型纸箱包装, 未达到整箱数量以产品量适当采用小型或中型纸箱包装.
10. PART NO. (零件料号):

Xihoy 深圳市鑫鸿源精密电子有限公司
Shenzhen Xinhongyuan Precision Electronics Co., Ltd.
财富热线电话: 13670232690
工厂地址: 深圳市宝安区新桥街道象山社区132号17栋7楼

PART NO	LW0540-** * *			4	STATOR	PHOSPHOR BRONZE		0	DAR. BY MR. ZHANG	DATE: 2016. 06. 08	UNLESS OTHERWISE SPECIFIED TOLERANCE			
PART NAME	0.5 Pitch无盖立式正脚位(H=4.0)			3	TERMINAL	PHOSPHOR BRONZE		POSITIONS			ANG	TOL	DMI	TOL
				2	COVER	THERMCPLASTIC UL94V-0	BLACK	1	CHK. BY MR. WANG	SCALE 1/1	. X	± 3.0°	. X	± 0.20
ANGLE PROJECTION		UNIT	mm	1	HOUSING	THERMCPLASTIC UL94V-0	NATURAL	0			APP. BY MISS. LU	UNIT MM	. XX	± 2.0°
		SCALE	1:1	NO.	COMPONENTS	MATERIALS	FINISH/COLOR SPECIFICATION	QUANTITY	. XXX	± 1.0°			. XXX	± 0.05